

ROLLER BLIND INFORMATION SHEET

Control Systems:

Manual: Chain Drive / Standard Spring Operation / Light Lift Motorisation: Acmeda, Somfy, Hunter Douglas, Louvolite – \$ refer to the Motorisation Sheet

Warranty:

Rollers and screens have a 5-year product guarantee – refer to product guarantee information. Please note that touching edges of cut fabric can cause fraying, if this occurs you will not be covered under warranty. 3000mm x 3500mm blinds can be manufactured but will not be covered under warranty.

Fixing and Allowances:

Face fix No allowances

Recess 5mm deducted of width and 10mm deducted off drop

Corner 90° Width – 75mm (approx. only, will vary depending on fabric used)

Sizes:

Minimum width: 500mm guaranteed (varies with certain fabrics)

Depends on fabric width - NB: Joins may be required with fabrics that are of small widths Maximum width:

Options:

Roller Fancy Trim Refer to Roller Fancy Trim Information sheet for variations – prices listed on Fancy Roller Sheet

Base rail Profiles: Round, Oval, Flat, D30, Silent Bar D30, Sewn Hem, Louvolite EasyFit, Louvolite Gemini

Base rail Colours: Pure White, Barley, Sandstone, Clear Anodised (Matt Silver), Black, Bone, Dune, Bronze Pearl,

Gemini - White, Clear Anodised, Black, Anthracite Grey

1 metre minimum charge - Clear Anodised (Matt Silver), Pure White, Sandstone and Black D30 Silent Bottom Rail

Double Bracket Slim Profile or Combo - Pure White, Sandstone, Clear Anodised (Matt Silver), Black

Stainless Steel Chain \$ refer to Stock List Louvolite EasyFit Bar 1 metre minimum charge Roller cloth only List price less 20%

Easylink - Independent or Multi-link Pure White, Barley, Sandstone, Clear Anodised (Matt Silver), Black

Easylink – Double Bearing Bracket

Booster Spring For blinds under the recommended weight limit of 2.5kgs

Zero Gravity Spring Operation System

Guide Wire System for Doors

60mm Tubing POA

Alterations:

All blinds will have a minimum charge plus parts and freight*

Note that any fabric that requires a cut back of less than 40mm each side will be hand cut which may result in fraying

*This is a guideline only; every application will vary, and quotations may be provided for authorisation