



## PANEL GLIDE INFORMATION SHEET

When Ordering Panel Glides please specify on your order:

**Finished Blind Size:**

Width of track and drop of blind from the top of track to the bottom of the blade

**Control side and draw configuration:**

One way draw (Left-hand or right-hand stack), Centre close or Centre stack (refer to Panel Glide Track Configuration sheet)

**Fixing and Allowances:**

Face fix	No allowances
Recess	5mm deducted of width and 10mm deducted off drop

**Sizes:**

Maximum recommended width	5000mm wide
Minimum recommended width	300mm wide

**Controls:**

If cord control is requested, the drop of the cord is 1500mm as standard unless specified otherwise  
When wand control is requested, the drop of the wand is 750mm unless specified otherwise.  
Cord Operation is an extra fee – POA.

**Options:**

Track Colours:	Pure White, Sandstone, Clear Anodised (Matt Silver) and Black
Base rail Profiles:	Round, Oval, Flat, D30, Sewn Hem, Louvolite EasyFit Bar
Base rail Colours:	Pure White, Barley, Sandstone, Clear Anodised (Matt Silver), Black, Bone, Dune, Bronze Pearl, Chrome (Round or Oval only)
Centre Close/Centre Stack	POA

**Alterations:**

All blinds will incur a minimum charge plus parts and freight + GST \*

Note that any fabric that requires a cut back of less than 40mm each side will be hand cut which may result in fraying

*\*This is a guideline only; every application will vary and quotations may be provided for authorisation*